

Heavy Duty Fixed Height Barrier with Swing Gate HBF-04

- A good security option for restricting both over height and unauthorised vehicles
- Gate can be locked when required (padlock not supplied)
- Restricts all types of vehicles when gate is locked, and high sided vehicles or caravans when open
- Available in economy or heavy duty options
- Available in sizes 3m – 7m
- Varying heights options available 1.9m to 2.4m
- Surface Fixed or Root Fixed options
- Galvanised and or Powdercoated / Painted options



Heavy Duty Height Restriction Barrier and Swing Gate combination is a highly effective deterrent for both controlling access to the carpark, as well as limiting the type of vehicles entering the area. The swing gate can be locked to prevent all access to the car park when required and opened to allow low vehicles access. This is a very popular option with country parks, schools, and public carparks with limited opening hours.

Manufactured from galvanised steel and painted finish to provide a durable and effective product. Optional extras available such as a painted finish, knocking bar, signage, and root fixed or surface fixed options and optional swing gate to prevent access during closing times

SPECIFICATION

Materials: 120 x 120 x 5mm Steel Box Section

Top Cross Bar: 60 x 60 x 3mm Steel Box Section

Swing Gate: 60 x 60 x 5mm Steel Box Section

Finish: Hot Dip Galvanised and or Painted

Surface mounted base plate: 500 x 500 x 10 with gusset steel construction



** Opening latch post – (strongly recommended) as a safety measure

** This product is supplied as Galvanised. If Powdercoated and Galvanised option is selected, this will have an additional cost and will extend the lead time. Please note that this product is not suitable for marine environments unless Galvanised and Powdercoated option is selected.

** Bespoke sizes are available and will be made to order. Please choose the next standard size up and specify on your order what exact size you require us to manufacture. Please note that if no bespoke size is selected, the height barrier will be made to the standard size selected.

Optional Extra's: Warning Signage, Knocking Bar, Manual Swing Gate, Opening Latch Post

Installation:

Root Fixed - Recommended size for the concrete foundation is 700x700x700mm deep as a minimum for main posts.

Opening latch post foundation should be a 300mm cube.

Surface Fixed - Main post requires 4 no 16mm bolts for the two upright posts. The base size is 400x400x10mm
 Catch post requires 4 no 12mm bolts